

# TEST ATTESTATION

Contract No.: 2392/2013/51/1 - RT

17.10.2014  
NEF/BAJ

Customer: Kaindl Flooring GmbH  
Kaindlstraße 2  
AT-5071 Wals/Salzburg

Subject: Laminate floor No. 51 of the type „Kaindl Laminate FLOORING  
Natural Touch 10.0 Premium Plank“  
Test according to OENORM EN 13329 „Laminate floor  
coverings - Specifications, requirements and test methods“


Result:

Classification requirements		
Wear resistance	AC5	
Impact resistance	IC3	
Resistance to staining	Group 1 and 2	level 5
	Group 3	level 4
Resistance to cigarette burns	level 4	
Effect of a furniture leg	no damage is visible	
Effect of a castor chair	no damage is visible	
Thickness swelling	≤ 18,0%	


The tested laminate floor fulfils all requirements of OENORM EN 13329 for the level of use class 33. The formaldehyde release determined according to OENORM EN 717-2 is below the allowable limit for faced wood-based panels which is given in the Austrian formaldehyde regulation and in DIBt-Guideline 100 (E1). Since 01.01.2009 substrates certified according to CCR, Title 17 93120.2(a) Phase 2 (CARB Regulation) are used by the manufacturer. Usage and conformity of the substrates are subject to regular tests and plant audits by Holzforschung Austria (CARB TPC-11). Measured contents of heavy metals (Sb, As, Ba, Cd, Cr, Pb, Hg, Se) are below the requirements of OENORM EN 71-3:2002. The formaldehyde emission determined according to the desiccator method (JIS A 1460) met the limit value of ≤ 0,3 mg/l.

Period of validity: June 2015

HOLZFORSCHUNG AUSTRIA



Dr. Georg Oberdorfer  
Technical consultant



Dr. Franz Neumueller  
Technical consultant

In case of dispute the original German version prevails. This translation is for information purposes only.